

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor

CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6520UE	2	solid	U-1000 1000	U-305 305	10.0 9.0	4.5 4.1	.015	.38	.118	3.00
6500UE	2	7	C-500 C-1000 U-1000 1000	C-152 C-305 U-305 305	4.5 9.0 10.0 10.0	2.0 4.1 4.5 4.5	.015	.38	.124	3.15
6521UE	3	solid	1000	305	13.0	5.9	.015	.38	.125	3.18
6501UE	3	7	U-1000 1000	U-305 305	14.0 13.0	6.4 5.9	.015	.38	.131	3.33
6522UE	4	solid	U-500 U-1000 1000	U-152 U-305 305	8.5 17.0 16.0	3.9 7.7 7.3	.015	.38	.136	3.45
6502UE	4	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	8.0 9.0 8.5 17.0 17.0	3.6 4.1 3.9 7.7 7.7	.015	.38	.143	3.63
6524UE	6	solid	C-500 U-1000	C-152 U-305	10.5 23.0	4.8 10.5	.015	.38	.162	4.11
6504UE	6	7	C-500 500 U-1000 1000	C-152 152 U-305 305	11.0 12.0 24.0 24.0	5.0 5.5 10.9 10.9	.015	.38	.171	4.34
6506UE	8	7	U-500 U-1000 1000	U-152 U-305 305	15.5 30.0 31.0	7.0 13.6 14.1	.015	.38	.186	4.72
6508UE	10	7	U-1000 1000	U-305 305	37.0 43.0	16.8 19.5	.015	.38	.218	5.54
6509UE	12	7	U-500 U-1000 1000	U-152 U-305 305	22.5 43.0 45.0	10.2 19.5 20.4	.015	.38	.225	5.72
20 AWG										
6400UE	2	7	C-500 500 U-1000 1000	C-152 152 U-305 305	6.0 7.0 14.0 14.0	2.7 3.2 6.4 6.4	.015	.38	.138	3.51
6401UE	3	7	U-1000 1000 5000	U-305 305 1524	19.0 18.0 90.0	8.6 8.2 40.9	.015	.38	.146	3.71
6402UE	4	7	U-1000 1000	U-305 305	24.0 24.0	10.9 10.9	.015	.38	.160	4.06
6403UE	5	7	U-1000 1000	U-305 305	28.0 28.0	12.7 12.7	.015	.38	.176	4.47
6406UE	8	7	1000	305	44.0	20.0	.015	.38	.209	5.31

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor (cont'd.)
CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CMP and CEC CMP FT6)

18 AWG										
6320UE	2	solid	U-1000	U-305	17.0	7.7	.015	.38	.147	3.73
6300UE*	2	7	C-500	C-152	8.0	3.6	.015	.38	.157	3.99
			U-500	U-152	9.5	4.3				
			500	152	9.0	4.1				
			U-1000	U-305	18.0	8.2				
			1000	305	18.0	8.2				
			5000	1520	90.0	40.8				
6321UE	3	solid	U-1000	U-305	24.0	10.9	.015	.38	.156	3.96
			1000	305	24.0	10.9				
6301UE	3	7	500	152	12.5	5.7	.015	.38	.168	4.27
			U-1000	U-305	25.0	11.4				
			1000	305	25.0	11.4				
6322UE	4	solid	U-1000	U-305	30.0	13.6	.015	.38	.171	4.34
6302UE	4	7	C-250	C-76	8.5	3.9	.015	.38	.186	4.72
			C-500	C-152	17.0	7.7				
			U-500	U-152	18.5	8.4				
			500	152	18.5	8.4				
			U-1000	U-305	36.0	16.4				
			1000	305	39.0	17.7				
			5000	1524	180.0	81.7				
6303UE	5	7	U-1000	U-305	39.0	17.7	.015	.38	.203	5.16
			1000	305	40.0	18.1				
6304UE	6	7	U-500	U-152	23.5	10.7	.015	.38	.222	5.64
			500	152	23.0	10.4				
			1000	305	51.0	23.2				
6306UE	8	7	500	152	30.5	13.9	.015	.38	.242	6.15
			1000	305	65.0	29.5				
6307UE	9	7	1000	305	68.0	30.9	.015	.38	.262	6.65
6308UE	10	7	1000	305	75.0	34.1				
6309UE	12	7	1000	305	84.0	38.2	.015	.38	.296	7.52
16 AWG										
6200UE	2	19	500	152	13.0	5.9	.015	.38	.180	4.57
			U-1000	U-305	25.0	11.3				
			1000	305	26.0	11.8				
6201UE	3	19	500	152	18.0	8.2	.015	.38	.191	4.85
			U-1000	U-305	36.0	16.4				
			1000	305	37.0	16.8				
6202UE	4	19	500	152	24.0	10.9	.015	.38	.211	5.36
			U-1000	U-305	46.0	20.9				
			1000	305	52.0	23.6				

*6300UE also available in Gray and Black.

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Multi-conductor CL2P Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, Natural Flamarrest jacket, rip cord. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.011" (.279mm)
Jacket	Flamarrest
Approvals	
NEC	CL2P
NEC Articles	725
Voltage Rating	150V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC CL2P)

14 AWG										
6100UE	2	19	500	152	19.5	8.8	.015	.38	.222	5.64
			U-1000	U-305	38.0	17.2				
			1000	305	38.0	17.2				
			5000	1524	195.0	88.5				
6101UE	3	19	1000	305	56.0	25.4	.015	.38	.236	5.99
6102UE	4	19	1000	305	73.0	33.2	.015	.38	.261	6.63
12 AWG										
6000UE	2	19	500	152	32.0	14.5	.015	.38	.256	6.50
			1000	305	58.0	26.4				
6001UE	3	19	1000	305	83.0	37.7	.015	.38	.273	6.93
6002UE	4	19	1000	305	111.0	50.4	.018	.46	.308	7.82

Color Code Chart

Cond. No.	Color
1	Black
2	White
3	Red
4	Green

Security and Alarm Cable

Commercial Applications
Shielded, Plenum-Rated



Shielded Multi-conductor CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, overall Beldfoil® tape shield (foil side out) and drain wire, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C


Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6520FE	2	solid	C-500	C-152	6.0	2.7	.015	.38	.122	3.10
			C-1000	C-305	12.0	5.4				
			U-1000	U-305	13.0	5.9				
			1000	305	13.0	5.9				
6500FE	2	7	C-500	C-152	5.5	2.5	.015	.38	.128	3.25
			U-500	U-152	7.0	3.2				
			500	152	7.0	3.2				
			C-1000	C-305	11.0	5.0				
			U-1000	U-305	13.0	5.9				
			1000	305	13.0	5.9				
6521FE	3	solid	1000	305	16.0	7.3	.015	.38	.129	3.28
6501FE	3	7	500	152	8.0	3.6	.015	.38	.135	3.43
			U-1000	U-305	16.0	7.3				
			1000	305	16.0	7.3				
6502FE	4	7	C-500	C-152	9.0	4.1	.015	.38	.147	3.73
			500	152	10.0	4.5				
			U-1000	U-305	19.0	8.6				
			1000	305	20.0	9.1				
6504FE	6	7	C-500	C-152	9.0	4.1	.015	.38	.175	4.45
			U-500	U-152	13.5	6.1				
			500	152	13.5	6.1				
			U-1000	U-305	26.0	11.8				
			1000	305	26.0	11.8				
6506FE	8	7	U-1000	U-305	33.0	15.0	.015	.38	.190	4.83
			1000	305	35.0	15.9				
6508FE	10	7	U-1000	U-305	40.0	18.1	.015	.38	.222	5.64
			1000	305	42.0	19.0				
20 AWG										
6420FE	2	solid	C-500	C-152	7.0	3.2	.015	.38	.134	3.40
			U-1000	U-305	16.0	7.3				
			1000	305	15.0	6.8				
6400FE	2	7	C-500	C-152	7.5	3.4	.015	.38	.142	3.61
			U-1000	U-305	17.0	7.7				
			1000	305	17.0	7.7				
6401FE	3	7	U-1000	U-305	21.0	9.5	.015	.38	.150	3.81
			1000	305	22.0	10.0				
6402FE	4	7	U-1000	U-305	26.0	11.8	.015	.38	.164	4.17
			1000	305	27.0	12.3				
6405FE	7	7	1000	305	41.0	18.6	.015	.38	.196	4.97
6407FE	9	7	1000	305	52.0	23.6	.015	.38	.229	5.82

Security and Alarm Cable

Commercial Applications
Shielded, Plenum-Rated



Shielded Multi-conductor (cont'd.)
CMP FT6 Rated or CL2P Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, overall Beldfoil® tape shield (foil side out) and drain wire, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	
18 and 16 AWG	.009" (.229mm)
14 and 12 AWG	.011" (.279mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC (18 and 16 AWG)	CMP
CEC (18 and 16 AWG)	CMP FT6
NEC (14 and 12 AWG)	CL2P
NEC Articles	
18 and 16 AWG	800
14 and 12 AWG	725
Voltage Rating	
18 and 16 AWG	300V
14 and 12 AWG	150V
Temperature Rating	75°C

Applications


- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Shorting Fold

Stranded Conductor



Shorting Fold

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

18 AWG										
6320FE	2	solid	C-500 1000	C-152 305	10.5 22.0	4.8 10.0	.015	.38	.150	3.89
6300FE	2	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	11.0 12.0 12.0 23.0 23.0	5.0 5.4 5.4 10.4 10.4	.015	.38	.162	4.11
6301FE	3	7	U-500 U-1000 1000	U-152 U-305 305	15.5 30.0 31.0	7.0 13.6 14.1	.015	.38	.172	4.37
6302FE	4	7	C-250 U-500 500 U-1000 1000	C-76 U-152 152 U-305 305	8.8 19.5 19.0 37.0 37.0	4.0 8.9 8.6 16.8 16.8	.015	.38	.188	4.78
6304FE	6	7	C-250 U-500 1000	C-76 U-152 305	12.0 25.5 52.0	5.4 11.6 23.6	.015	.38	.226	5.74
6306FE	8	7	1000	305	66.0	30.0	.015	.38	.246	6.25
6307FE	9	7	500 1000	152 305	39.5 73.0	18.0 33.2	.015	.38	.266	6.76
6309FE	12	7	500 1000	152 305	50.5 99.0	22.9 45.0	.018	.46	.306	7.77
16 AWG										
6200FE	2	19	500 1000	152 305	16.5 33.0	7.5 15.0	.015	.38	.184	4.67
6201FE	3	19	500 U-1000 1000	152 U-305 305	22.5 43.0 45.0	10.2 19.5 20.5	.015	.38	.195	4.95
6202FE	4	19	500 1000	152 305	29.0 59.0	13.2 26.8	.015	.38	.215	5.46

Shielded Multi-conductor (NEC CL2P)

14 AWG										
6100FE	2	19	500 U-1000 1000	152 U-305 305	25.0 49.0 51.0	11.3 22.2 23.1	.015	.38	.220	5.59
6101FE	3	19	1000	305	66.0	29.9	.015	.38	.234	5.94
12 AWG										
6000FE	2	19	500 1000	152 305	36.0 68.0	16.4 30.9	.015	.38	.260	6.60

Color Code Chart (18 to 16 AWG)

Cond. No.	Color	Cond. No.	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

(14 to 12 AWG)

Cond. No.	Color
1	Black
2	White
3	Red

Security and Alarm Cable

Commercial Applications
Unshielded, Plenum-Rated



Unshielded Twisted Pairs

CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, twisted into pairs, multiple pairs cabled together, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C


Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Pair No.	Color Combination	Pair No.	Color Combination
1	Black & Red	6	Black & Brown
2	Black & White	7	Black & Orange
3	Black & Green	8	Red & White
4	Black & Blue	9	Red & Green
5	Black & Yellow		

Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Twisted Pairs (NEC CMP and CEC CMP FT6)

22 AWG										
6561UE	2	solid	1000	305	19.0	8.6	.015	.38	.188	4.78
6541UE	2	7	U-1000 1000	U-305 305	19.0 20.0	8.6 9.1	.015	.38	.199	5.05
6542UE	3	7	1000	305	27.0	12.2	.015	.38	.212	5.38
6543UE	4	7	1000	305	34.0	15.4	.015	.38	.234	5.94
6545UE	6	7	1000	305	47.0	21.4	.015	.38	.264	6.71
6547UE	9	7	1000	305	69.0	31.4	.018	.46	.318	8.08
18 AWG										
6341UE	2	7	500 U-1000 1000	152 U-305 305	21.0 36.0 38.0	9.5 16.3 17.3	.015	.38	.260	6.60
6342UE	3	7	U-1000 1000	U-305 305	48.0 50.0	21.8 22.7	.015	.38	.278	7.06
6343UE	4	7	500 1000	152 305	37.5 66.0	17.0 30.0	.015	.38	.314	7.98
6345UE	6	7	1000	305	95.0	43.2	.018	.46	.355	9.02
6347UE	9	7	1000	305	138.0	62.7	.019	.48	.423	10.74

Security and Alarm Cable

Commercial Applications

Shielded, Plenum-Rated



Overall Shielded Twisted Pairs

CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, twisted into pairs, multiple pairs cabled together, overall Beldfoil® shield tape (foil side out) with drain wire, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C


Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Stranded Conductor



Color Code Chart

Pair No.	Color Combination	Pair No.	Color Combination
1	Black & Red	6	Black & Brown
2	Black & White	7	Black & Orange
3	Black & Green	8	Red & White
4	Black & Blue	9	Red & Green
5	Black & Yellow		

Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Overall Shielded Twisted Pairs (NEC CMP and CEC CMP FT6)

22 AWG										
6561FE	2	solid	1000	305	21.0	9.5	.015	.38	.193	4.90
6541FE	2	7	U-500	U-152	11.5	5.2	.015	.38	.203	5.16
			U-1000	U-305	22.0	10.0				
			1000	305	23.0	10.4				
6542FE	3	7	U-1000	U-305	28.0	12.7	.015	.38	.216	5.49
			1000	305	29.0	13.2				
6543FE	4	7	U-1000	U-305	35.0	15.9	.015	.38	.238	6.05
			1000	305	41.0	18.6				
6545FE	6	7	U-1000	U-305	48.0	21.8	.015	.38	.268	6.80
			1000	305	50.0	22.7				
6547FE	9	7	1000	305	72.0	32.7	.018	.46	.323	8.20
20 AWG										
6441FE	2	7	1000	305	31.0	14.1	.015	.38	.228	5.79
6443FE	4	7	U-1000	U-305	49.0	22.2	.015	.38	.269	6.83
			1000	305	51.0	23.2				
18 AWG										
6342FE	3	7	500	152	28.0	12.7	.015	.38	.282	7.16
			1000	305	56.0	25.5				
6343FE	4	7	500	152	39.5	18.0	.015	.38	.318	8.08
			1000	305	74.0	33.6				
6345FE	6	7	500	152	50.0	22.7	.018	.46	.359	9.12
			1000	305	101.0	45.9				
6347FE	9	7	1000	305	145.0	65.8	.019	.48	.427	10.85

Security and Alarm Cable

Commercial Applications
Shielded, Plenum-Rated



Shielded

Twisted Pair plus Conductor(s)

CMP FT6 Rated

Product Description

Bare copper conductors, Flamarrest® insulation, Black/Red twisted pair shielded with Beldfoil® tape (aluminum side facing in), drain wire, cabled with additional insulated conductor(s) as indicated, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.


Color Code: Black & Red pair, White, Green.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	.009" (.229mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls



Part No.	No. of Pairs + No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Twisted Pair plus Conductor(s) (NEC CMP and CEC CMP FT6)

22 AWG

6501GE	1 STP +1/C	7	1000	305	18.0	8.2	.015	.38	.174	4.42
---------------	------------	---	------	-----	------	-----	------	-----	------	------

6502GE	1 STP +2/C	7	U-1000 1000	U-305 305	21.0 21.0	9.5 9.5	.015	.38	.180	4.57
---------------	------------	---	----------------	--------------	--------------	------------	------	-----	------	------

20 AWG

6401GE	1 STP +1/C	7	1000	305	24.0	10.9	.015	.38	.195	4.95
---------------	------------	---	------	-----	------	------	------	-----	------	------

STP = Shielded Twisted Pair(s) • /C = Conductor(s)

Communication and Control Cable

Pro Audio and Intercom Systems
Unshielded, Plenum-Rated



**Unshielded,
Pairs or Multi-conductor**
CMP Rated

Product Description

24 AWG solid bare copper conductors,
FEP insulation, Dark Gray Flamarrest® jacket
with rip cord.

Color Code: See Charts below.


Specifications

Conductor	Bare Copper
Insulation	FEP
Insulation Thickness	.007" (.178mm)
Jacket	Flamarrest
Nominal Capacitance	15 pF/ft.
Approvals	
NEC	CMP
CEC	CMP FT6
Voltage Rating	300V


Applications

- Nurse Call Systems
- Commercial Sound Systems
- Annunciators
- Voice Systems
- Paging

Paired



Multi-conductor



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Plenum-rated, Unshielded, Pairs (NEC CMP and CEC CMP FT4, FT6)

24 AWG, Cat. 5e

6662UG new	6	solid	1000	304.8	23.0	10.4	—	—	.165	4.19
	(3/pr)									

Plenum-rated, Unshielded, Multi-conductor (NEC CMP and CEC CMP FT6)

24 AWG

6626UG new	8	solid	1000	304.8	28.0	12.70	.019	.483	.072	1.83
									X	X
									.310	7.87
6624UG new	6	solid	1000	304.8	21.0	9.53	.019	.483	.072	1.83
									X	X
									.246	6.25

Color Code Chart

(6662UG)

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green

Color Code Chart

(6626UG)

Cond. No.	Color
1	Yellow
2	Blue
3	Black
4	Orange
5	Red
6	Green
7	White
8	Purple

Color Code Chart

(6624UG)

Cond. No.	Color
1	Blue
2	Black
3	Orange
4	Red
5	Green
6	White

Communication and Control Cable

Pro Audio and Intercom Systems
Shielded, Plenum-Rated



Shielded Multi-conductor

CMP FT6 Rated

Product Description

Bare copper conductors, FEP insulation, conductors cabled with a Beldfoil® shield tape (foil side out) and drain wire. Natural Flamarrest® jacket with rip cord. Sequential footage marking every two feet.


Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	FEP
Insulation Thickness	
22 AWG	.0055" (.140mm)
20 AWG	.0060" (.152mm)
18 AWG	.0060" (.152mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Pro Audio Systems
- Intercom/PA Systems
- Security Systems



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6500FC	2	7	U-1000 1000	U-305 305	11.0 5.0	5.0 11.0	.015	.38	.116	2.95
6502FC	4	7	1000	305	18.0	8.2	.015	.38	.133	3.38
20 AWG										
6400FC	2	7	U-1000	U-305	15.0	6.8	.015	.38	.133	3.38
18 AWG										
6300FC	2	7	U-1000 1000	U-305 305	23.0 10.4	10.4 22.0	.017	.42	.155	3.94
6302FC	4	7	U-1000 1000	U-305 305	34.0 15.5	15.5 36.0	.017	.42	.179	4.55

Color Code Chart

Cond No.	Color
1	Black
2	Red
3	White
4	Green

Communication and Control Cable

Pro Audio and Intercom Systems
Overall Shielded, Plenum-Rated



Overall Shielded Pairs

CMP FT6 Rated

Product Description

Bare copper conductors, FEP insulation, twisted pairs cabled with a Beldfoil® shield tape (foil side out) and drain wire. Natural Flamarrest® jacket.

Color Code: Black & Red and Black & White pairs.

Specifications

Conductor	Bare Copper
Insulation	FEP
Insulation Thickness	.0060" (.152mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Pro Audio Systems
- Intercom/PA Systems
- Security Systems



Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Overall Shielded Pairs (NEC CMP and CEC CMP FT6)

24 AWG										
6641FC	2	7	U-500	U-152	8.0	3.6	.015	.38	.164	4.17

Communication and Control Cable

Pro Audio and Intercom Systems
Individually Shielded, Plenum-Rated



Individually Shielded Twisted Pairs CMP FT6 Rated

Product Description

Bare copper conductors, FEP insulation (per table). Conductors twisted into pairs and individually shielded with Beldfoil® tape (aluminum side facing in) and a drain wire, multiple pairs cabled together, Gray Fluorocopolymer (22 AWG) or Natural Flamarrest® (18 AWG) jacket, rip cord. Sequential footage marking every two feet.


Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	FEP
Insulation Thickness	.010" (.254mm)
Shield	Beldfoil
Jacket	
22 AWG	Gray Fluorocopolymer
18 AWG	Natural Flamarrest
Nominal Capacitance	
22 AWG	27.5 pF/ft.
18 AWG	44 pF/ft.
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls
- Analog Multi-pair Snakes



Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Individually Shielded Twisted Pairs (NEC CMP and CEC CMP FT6)

22 AWG										
6541PA	2	7	500	152	13.5	6.1	.015	.38	.214	5.44
			U-1000	U-305	26.0	11.8				
			1000	305	27.0	12.3				
6542PA	3	7	1000	305	36.0	16.3	.015	.38	.228	5.79
6543PA	4	7	1000	305	45.0	20.4	.015	.38	.252	6.40
6545PA	6	7	1000	305	60.0	27.2	.015	.38	.300	7.62
6546PA	8	7	1000	305	85.0	38.6	.017	.42	.332	8.43
6548PA	12	7	1000	305	125.0	56.8	.017	.42	.408	10.36
6549PA	16	7	1000	305	162.0	73.5	.017	.42	.457	11.61
18 AWG										
6341PC	2	7	500	152	26.5	12.0	.017	.42	.281	7.14
			U-1000	U-305	47.0	21.3				
			1000	305	49.0	22.2				
6342PC	3	7	500	152	32.0	14.5	.017	.42	.300	7.62
			1000	305	64.0	29.0				
6343PC	4	7	1000	305	83.0	37.7	.017	.42	.332	8.43
6345PC	6	7	500	152	66.5	30.2	.019	.48	.402	10.21
			1000	305	132.0	59.9				

Color Code Chart

Pair No.	Color Combination	Pair No.	Color Combination	Pair No.	Color Combination
1	Black & Red	6	Black & Brown	11	Red & Yellow
2	Black & White	7	Black & Orange	12	Red & Brown
3	Black & Green	8	Red & White	13	Red & Orange
4	Black & Blue	9	Red & Green	14	Green & White
5	Black & Yellow	10	Red & Blue	15	Green & Blue
				16	Green & Yellow

Thermostat & Control Cable

Commercial Applications
Shielded, Plenum-Rated



Overall Shielded Twisted Pairs CMP FT6 Rated

Product Description

Tinned copper conductors, Foam Fluorinated Ethylene Propylene (FFEP) insulation. Conductors twisted into pairs, overall Beldfoil® shield (100% coverage), tinned copper drain wire, overall Brown Flamarrest® jacket. Sequential footage marking every two feet.

Color Code: Black & White, Green & Red.

Specifications

Conductor	Bare Copper
Insulation	FFEP
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Thermostat and control cable

Stranded Conductor



Solid Conductor



Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Overall Shielded Twisted Pairs (NEC CMP and CEC CMP FT6)

24 AWG										
6660FT	1	solid	1000	305	11.0	5.0	.015	.38	.128	3.25
6661PT	2	solid	1000	305	19.0	8.6	.015	.38	.155	3.94
22 AWG										
6540FT	1	7	1000	305	32.0	6.8	.015	.38	.162	4.12
6541PT	2	7	1000	305	28.0	12.7	.015	.38	.192	4.88
18 AWG										
6340FT	1	7	1000	305	32.0	6.8	.015	.38	.260	6.60
6341PT	2	7	1000	305	60.0	27.2	.015	.38	.280	7.11

Access Control Banana Peel® Cable

Lock Power, Card Reader, Door Contact, REX Applications
Plenum-Rated



**Composite
Shielded Multi-Conductors**
CMP FT6 Rated

Product Description


Stranded bare copper conductors, Flammarrest® insulation and jackets. No overall jacket. All cables are Beldfoil® shielded (100% coverage) with drain wire and rip cord. Cable jackets are color coded by application. Individual jacket is sequentially marked at two foot intervals.

Specifications

Conductor	Bare Copper
Insulation	Flammarrest
Shield	Beldfoil
Individual Jackets	Flammarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Power-Limited Controls
- Access Control
- Card Reader
- Lock Power
- Door Control
- REX

**Individual Cable Jacket Color Coding System**

Jacket Color	Print Legend	Cable Type
Orange	Card Reader	3/P, 18 or 22 AWG, Shielded
White	Door Contact	2/C, 18 or 22 AWG, Shielded
Blue	Rex/Spare	4/C, 18 or 22 AWG, Shielded
Gray	Lock Power	4/C, 16 or 18 AWG, Shielded

Part No.	Component Descriptions	Insulation Material & (Color Code)	Jacket Material & Component OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	ft.	m	Lbs.	kg

Composite Shielded Multi-Conductors (NEC CMP and CEC CMP FT6)

(3) Shielded Multi-Conductors • (1) Shielded Multi-Pair										
658AFS new	(1) 3-Pair 22 AWG Stranded (7x30) Bare Copper Shielded	Flammarrest (Black & Red, White & Green, Orange & Brown)	Orange Flammarrest	.420	10.67		500	152	60	27.2
			.218	5.54			1000	304	113	51.3
	(1) 2-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	Flammarrest (Black, Red)	White Flammarrest	.131	3.33					
	(1) 4-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	Flammarrest (Black, Red, White, Green)	Blue Flammarrest	.150	3.81					
	(1) 4-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	Flammarrest (Black, Red, White, Green)	Gray Flammarrest	.191	4.85					
638AFS new	(1) 3-Pair 18 AWG Stranded (7x26) Bare Copper Shielded	Flammarrest (Black & Red, White & Green, Orange & Brown)	Orange Flammarrest	.542	13.77	1000	305	189	85.7	
			.291	7.39						
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	Flammarrest (Black, Red)	White Flammarrest	.168	4.27					
	(1) 4-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	Flammarrest (Black, Red, White, Green)	Blue Flammarrest	.197	5.00					
	(1) 4-Cond. 16 AWG Stranded (19x30) Bare Copper Shielded	Flammarrest (Black, Red, White, Green)	Gray Flammarrest	.224	5.69					

U.S. Patent 7,049,523

Security Composite Cable

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated and Non-Plenum



Non-Plenum Composite Coax plus Twisted Pair

CM FT1 or CMG-LS FT4 Rated

Product Description

Coax: Solid bare copper conductor, foam polyolefin insulation, bare copper braid shield. Black PVC jacket (1306SB has Black LSZH jacket).

Pair: Stranded bare copper conductor, PVC insulation, Black PVC jacket. (1306SB has polypropylene insulation. Black LSZH jacket.) Color coded: Black & Red.

Plenum-Rated Composite Coax plus Twisted Pair

CMP FT6 Rated

Product Description

Coax: Solid bare copper conductor, FEP insulation, bare copper braid shield, Natural Flammarrest® jacket.

Pair: Stranded FEP insulation, Natural Flammarrest jacket. Color coded: Black & Red.

Coax and pair in Siamese configuration.
Sequential footage marking every two feet.

Specifications

Conductor	Bare Copper
Insulation (Non-Plenum)	
Coax	FPO
Pair	PVC
Insulation (Plenum)	FEP
Shield (Coax)	Bare Copper Braid
Jacket	
Non-Plenum	PVC
Plenum	Flammarrest
Approvals (Non-Plenum)	
NEC	CM
CEC	CM FT1
Approvals (LSZH)	
NEC	CMG-LS
CEC	CMG-LS FT4 Limited Smoke
Approvals (Plenum)	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Nominal Impedance (Coax)	75Ω
Temperature Rating	75°C

Applications

- CCTV plus Audio or Power
- Pan, Tilt and Zoom CCTV Control



Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

CM-Rated Composite (NEC CM and CEC CM FT1)

Mini RG-59 Type

579945 new	25(cx)	solid BC	95% BC	.085	2.16	.151	3.84	500	152	15.0	6.8
	20(pr)	7/w BC	unshielded	.056	1.42	x	x	1000	305	29.0	13.2
						.332	8.43				

RG-59 Type

549945	20(cx)	solid BC	95% BC	.145	3.68	.232	5.89	500	152	30.0	13.6
	18(pr)	7/w BC	unshielded	.066	1.68	x	x	1000	305	60.0	27.3
						.460	11.68				

RG-6 Type

539945	18(cx)	solid BC	95% BC	.180	4.57	.266	6.76	500	152	34.0	15.5
	18(pr)	7/w BC	unshielded	.066	1.68	x	x	1000	305	69.0	31.3
						.500	12.70				

CMG-LS -Rated Composite (NEC CMG-LS and CEC CMG-LS FT4 Limited Smoke)

RG-6 Type

1306SB new	18(cx)	solid BC	95% BC	.180	4.57	.275	6.99	500	152	37.0	16.8
	18(pr)	7/w BC	unshielded	.059	1.59	x	x	1000	305	76.0	34.5
						.514	13.06				

Plenum-Rated Composite (NEC CMP and CEC CMP FT6)

Mini RG-59 Type

679948* new	25(cx)	solid BC	95% BC	.078	1.98	.144	3.66	500	152	16.5	7.4
	20(pr)	7/w BC	unshielded	.048	1.22	x	x	1000	305	34.0	15.5
						.328	8.33				

RG-59 Type

649948	20(cx)	solid BC	95% BC	.134	3.40	.199	5.05	500	152	29.0	13.2
	18(pr)	7/w BC	unshielded	.059	1.50	x	x	1000	305	54.0	24.5
						.383	9.72				

RG-6 Type

639948	18(cx)	solid BC	95% BC	.170	4.32	.232	5.89	500	152	32.0	14.5
	18(pr)	7/w BC	unshielded	.059	1.50	x	x	1000	305	60.0	27.2
						.416	10.57				

BC = Bare Copper • cx = Coax • pr = Pair • LSZH = Low-Smoke, Zero-Halogen

*679948 also available in White.

Security Coaxial Cable

CCTV and Card Reader/Sensor Applications
Plenum-Rated



Plenum-Rated Coax

CMP FT6 Rated

Product Description

Bare copper or copper-covered steel conductor, foam FEP insulation, bare copper braid shield. Natural Flamarrest® jacket (except 613948 which is White fluorocopolymer). Sequential footage marking every two feet.

Specifications

Conductor	Solid BC or BCCS
Insulation	Foam FEP
Shield	Bare Copper Braid
Jacket	Flamarrest†
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Nominal Impedance	75Ω
Nominal Impedance (6539Y8 only)	93Ω
Temperature Rating	75°C

†613948 jacket is White fluorocopolymer.

Applications

- CCTV
- Card Reader/Sensor (6539Y8)



Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-Rated Coax for CCTV (NEC CMP and CEC CMP FT6)

Mini RG-59 Type

673948	25	solid BC	95% BC	.078	1.98	.146	3.71	U-500	U-152	9.0	4.1
								U-1000	U-305	17.0	7.7
								1000	305	17.0	7.7

RG-59 Type

643948*	20	solid BC	95% BC	.135	3.43	.193	4.90	U-500	U-152	16.0	7.3
								500	152	17.5	8.0
								U-1000	U-305	30.0	13.6
								1000	305	32.0	14.5

RG-6 Type

633948	18	solid BC	95% BC	.170	4.32	.228	5.79	U-500	U-152	20.5	9.8
								500	152	20.5	9.8
								U-1000	U-305	40.0	18.1
								1000	305	42.0	19.1

RG-11 Type

613948	14	solid BC	95% BC	.274	6.96	.348	8.84	500	152	44.5	20.2
								1000	305	90.0	40.9

*643948 also available in Black jacket.

Plenum-Rated Coax for Card Readers/Sensors (NEC CMP, CEC CMP FT6)

RG-62 Type

6539Y8	22	solid BCCS	95% BC	.146	3.71	.204	5.18	U-1000	U-305	31.0	14.1
								1000	305	33.0	15.0

BC = Bare Copper • BCCS = Bare Copper-covered Steel

Security UTP CableCCTV Fixed and PTZ Applications
Plenum-Rated**Plenum-Rated**

CMP Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, FEP Teflon® insulation, Flamarrest® jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- Pan/Tilt/Zoom (PTZ)



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-Rated (NEC CMP and CEC CMP FT6)**Category 5e**

1585A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.007	0.18	.195	4.95	U-1000 1000 3000	U-305 305 915	23.0 24.0 69.0	10.4 10.9 31.3
------------------------------------	---	------------	------	------	------	------	------------------------	---------------------	----------------------	----------------------

1501A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.008	0.20	.195	4.95	A-1000 1000	A-305 305	26.0 23.0	11.8 10.4
------------------------------------	---	------------	------	------	------	------	----------------	--------------	--------------	--------------

Category 6

7882A new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP Teflon	.009	0.23	.224	5.69	A-1000 1000	A-305 305	32.0 29.0	14.5 13.2
------------------------------------	---	------------	------	------	------	------	----------------	--------------	--------------	--------------

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.**Color Code Chart**

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



**Composite Coax,
Pair and Multi-Conductors**
CMP FT6 Rated

Product Description

(1) **Coax:** 20 AWG solid bare copper conductor, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) **Pair:** 23 AWG solid bare copper conductors, FEP insulation, Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) **Conductors:** 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Unshielded
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control



Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 23 AWG Pair • 18 AWG Cond.										
600PTZ new	(1) Coax: RG-59/U 20 AWG (solid) Bare Copper Cond.	FPFA, Bare Copper Braid Shield (95% coverage)	.193	4.90	.351	8.9	500	152	38.5	17.5
	(1) 1-Pair 23 AWG (solid) Bare Copper Cond.	FEP, Unshielded	.116	2.95			1000	305	71.0	32.2
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Cond.	Flamarrest, Unshielded	.158	4.01						

FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

U.S. Patent 7,049,523

Individual Cable Jacket Color Coding System

Jacket Color	Cable Type
Black	Coax, RG-59/U, 20 AWG, BC Braid (95%)
Blue	1/P, 23 AWG, Unshielded
White	2/C, 18 AWG, Unshielded

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



**Composite Coax,
Pair and Multi-Conductors**
CMP FT6 Rated

Product Description

(1) **Coax:** 20 AWG solid bare copper conductor, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) **Pair:** 22 AWG stranded (7x30) bare copper conductors, FEP insulation, Beldfoil® shield (100% coverage), Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) **Conductors:** 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control

**Individual Cable Jacket Color Coding System**

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 22 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 22 AWG Pair • 18 AWG Cond.										
601PTZ new	(1) Coax: RG-59/U 20 AWG (solid) BC Cond.	FPFA, BC Braid Shield (95% coverage)	.193	4.90	.351	8.9	500	152	40.0	18.2
	(1) 1-Pair 22 AWG (7x30) BC Cond.	FEP, Beldfoil Shield (100% coverage)	.116	2.95			1000	305	73.0	33.2
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	Flamarrest, Unshielded	.158	4.01						

BC = Bare Copper • FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

U.S. Patent 7,049,523

Pan/Tilt/Zoom Banana Peel® Composite

CCTV plus Audio or Power or Pan and Tilt CCTV Control Applications
Plenum-Rated



**Composite Coax,
Pair and Multi-Conductors**
CMP FT6 Rated

Product Description

(1) Coax: 20 AWG solid bare copper conductors, Foam Perfluoroalkoxy (FPFA) insulation, bare copper braid shield (95% coverage), Black Flamarrest® jacket.

(1) Pair: 18 AWG stranded (19x30) bare copper conductor, FEP insulation, Beldfoil® shield (100% coverage), Blue Flamarrest jacket. Color code: White/Blue Stripe & Blue. Category 5e tested.


(2) Conductors: 18 AWG stranded (7x26) bare copper conductors, Flamarrest insulation, White Flamarrest jacket. Color code: Black & Red.

Specifications

Conductor	Bare Copper
Application Shielding	
Video	Bare Copper Braid
Control	Aluminum/Polyester
Power	Unshielded
Component Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- CCTV plus Control and Power
- Pan, Tilt and Zoom CCTV Control

**Individual Cable Jacket Color Coding System**

Jacket Color	Cable Type
Black	Coax: RG-59/U, 20 AWG, BC Braid Shield
Blue	1/P, 18 AWG, Beldfoil Shield
White	2/C, 18 AWG, Unshielded

Banana Peel is patent pending.

Part No.	Component Descriptions	Insulation Material & Shielding	Component Nom. OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-rated Composite (NEC CMP and CEC CMP FT6)

RG-59/U 20 AWG Coax • Cat. 5e 18 AWG Pair • 18 AWG Cond.										
602PTZ new	(1) Coax: RG-59/U	FPFA, BC Braid Shield (95% coverage)	.193	4.90	.363	9.2	500	152	42.5	19.3
	20 AWG (solid) BC Cond.						1000	305	79.0	35.8
	(1) 1-Pair 18 AWG (19x30) BC Cond.	FEP, Beldfoil Shield (100% coverage)	.150	3.81						
	(1) 2-Cond. 18 AWG Stranded (7x26) BC Cond.	Flamarrest, Unshielded	.158	4.01						

BC = Bare Copper • FEP = Fluorinated Ethylene Propylene • FPFA = Foam Perfluoroalkoxy

Security Coaxial Cable

Commercial CATV or MATV Applications
Plenum-Rated



Plenum-Rated Coax

CMP FT6 Rated

Product Description

Solid bare copper conductor. Foam FEP insulation. Foil plus aluminum braid shield(s) as indicated. Natural Flamarrest® jacket (except 6139B8 which is White fluorocopolymer). Sequential footage marking every two feet.

Specifications

Conductor	Solid BC or BCCC
Insulation	Foam FEP
Shield	Duofoil® + Aluminum Braid(s)
Jacket	Flamarrest†
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	820
Nominal Impedance	75Ω
Temperature Rating	75°C

†6139B8 jacket is White fluorocopolymer.

Applications

- CATV
- MATV

Duofoil + Braid Shield



Quad Shield



Part No.	AWG	Stranding and Conductor	Shield/Braid Coverage	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
				Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Plenum-Rated Coax (NEC CMP and CEC CMP FT6)

Series 59 • RG-59 Type

6439C8	20	solid BC	Duofoil + 80% AL braid	.135	3.43	.199	5.05	1000	305	20.0	9.1
---------------	----	----------	------------------------	------	------	------	------	------	-----	------	-----

6439Q8	20	solid BC	Quad*	.135	3.43	.223	5.66	U-1000	U-305	24.0	10.9
---------------	----	----------	-------	------	------	------	------	--------	-------	------	------

Series 6 • RG-6 Type

633938	18	solid BC	Duofoil + 90% AL braid	.170	4.32	.233	5.92	U-500	U-152	15.0	6.8
								500	152	15.0	6.8
								U-1000	U-305	29.0	13.2
								1000	305	29.0	13.2

6339Q8	18	solid BCCC	Quad*	.170	4.32	.248	6.30	U-1000	U-305	30.0	13.6
								1000	305	32.0	14.5

Series 11 • RG-11 Type

6139B8	14	solid BC	Duofoil + 60% AL braid	.274	6.96	.348	8.84	1000	305	66.0	30.0
---------------	----	----------	------------------------	------	------	------	------	------	-----	------	------

AL = Aluminum • BC = Bare Copper • BCCC = Bare Copper Center Conductor

*Quad Shield: Duofoil tape + 60% copper braid + Duofoil tape + 40% copper braid.

UTP CCTV Surveillance Cables

CCTV and PTZ Applications
Unshielded, Plenum-Rated



Composite
Unshielded Multi-conductor
CMP Rated

Product Description

Data Pair: 24 or 23 AWG solid bare copper conductors, unshielded twisted pairs, FEP insulation.

Power Conductors: 16 AWG stranded (19x29) tinned copper conductors, unshielded, FEP or Flammarrest® insulation.




Overall: White or Black, Flammarrest jacket.

Specifications

Conductor	
Data Pair	Solid Bare Copper
Power	Stranded Tinned Copper
Shield	Unshielded
Jacket	Flammarrest
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- UTP-CCTV
- CCTV
- CCTV on UTP
- CCTV Video/Control
- Closed Circuit Television
- Pan/Tilt/Zoom (PTZ) Cameras
- Surveillance
- Video Over Twisted Pairs

6284UE (Round Construction)**6284US (Siamese Construction)****6288US (Siamese Construction)**

Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Composite (NEC CMP and CEC CMP)

Category 5e										
6284UE new	2-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP	.041	1.04	.220	5.59	500 1000	152 305	19.5 38.0	8.8 17.2
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	FEP	.077	1.96						
6284US new	2-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP	.035	.89	.173 x .358	4.39 x 9.09	500 1000	152 305	26.0 50.0	11.8 22.7
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	Flamarrest	.077	1.96						
6288US new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP	.042	1.07	.222 x .450	5.64 x 11.43	500 1000	152 305	34.5 66.0	15.7 29.9
	2-Cond. 16 AWG Stranded (19x29) Tinned Copper Cond.	Flamarrest	.077	1.96						

FEP = Fluorinated Ethylene Propylene • UTP = Unshielded Twisted Pair

Color Code Chart (Data Pair)

Pair No.	Color
1	Blue & White/Blue Stripe
2	Orange & White/Orange Stripe
3	Green & White/Green Stripe
4	Brown & White/Brown Stripe

Color Code Chart (Power)

Cond. No.	Color
1	Black
2	Red

UTP CCTV Surveillance Cables

CCTV Fixed and PTZ Applications
Unshielded, Plenum-Rated

**Unshielded Twisted Pairs**

CMP Rated

Product Description


Solid bare copper conductors, unshielded twisted pairs, FEP Teflon® insulation, Flamarrest® jacket with rip cord. Sequential footage marking every two feet.

Specifications

Conductor	Solid Bare Copper
Shield	Unshielded
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP
NEC Articles	800
Nominal Impedance	100Ω
Temperature Rating	75°C

Applications:

- 100BaseTX
- 100BaseVG ANYLAN
- 155ATM
- 622ATM
- AES/EBU
- Digital Video, RS-422
- Gigabit Ethernet
- NTSC/PAL Component or Composite Video
- Premise Horizontal Cable
- CCTV UTP
- Pan/Tilt/Zoom (PTZ)



Part No.	Component Descriptions	Insulation Material	Insulation Nominal OD		Nominal OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Unshielded Twisted Pairs (NEC CMP and CEC CMP FT6)**Category 5e**

1585A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon®	.007	0.18	.195	4.95	U-1000 1000 3000	U-305 305 915	23.0 24.0 69.0	10.4 10.9 31.3
------------------------------------	---	-------------	------	------	------	------	------------------------	---------------------	----------------------	----------------------

1501A new	4-Pair UTP 24 AWG Solid Bare Copper Cond.	FEP Teflon	.008	0.20	.195	4.95	A-1000 1000	A-305 305	27.0 24.0	12.2 10.9
------------------------------------	---	------------	------	------	------	------	----------------	--------------	--------------	--------------

Category 6

7882A new	4-Pair UTP 23 AWG Solid Bare Copper Cond.	FEP Teflon	.009	0.23	.224	5.69	A-1000 1000	A-305 305	34.0 31.0	15.4 14.1
------------------------------------	---	------------	------	------	------	------	----------------	--------------	--------------	--------------

UTP = Unshielded Twisted Pair

Refer to www.belden.com for jacket colors and put-ups.

Color Code Chart

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.

Fire Alarm Cable

Commercial Applications

Unshielded or Shielded, Plenum-Rated, Power-Limited



Unshielded or Shielded Multi-conductor FPLP Rated

Product Description

Bare copper conductors, Flamarrest® insulation, cabled together, Red Flamarrest jacket with rip cord. Shielded version has overall Beldfoil® shield tape (foil side out) and drain wire. Sequential footage marking every two feet.

Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Shield (where applicable)	Beldfoil
Jacket	Flamarrest
Jacket Thickness	.015" (.381mm)
Approvals	
NEC	FPLP
California State Fire Marshall	
NEC Articles	760
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Fire Protection
- Alarm
- Signal
- Monitor/Detection
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

Unshielded



Shielded



Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	6	Yellow
2	Red	7	Purple
3	Brown	8	Green
4	Blue	9	Red/Black
5	Orange	10	Red/White

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC FPLP)

22 AWG										
6522UL	4	solid	U-1000 1000	U-305 305	17.0 16.0	7.7 7.3	.009	.23	.136	3.45
6524UL	6	solid	C-500 U-1000 1000	C-152 U-305 305	10.5 22.0 22.0	4.8 10.0 10.0	.009	.23	.162	4.12
18 AWG										
6320UL*	2	solid	C-500 U-500 U-1000 1000	C-152 U-152 U-305 305	8.0 9.0 18.0 17.0	3.6 4.1 8.2 7.7	.010	.25	.151	3.84
6321UL	3	solid	1000	305	28.0	12.7	.010	.25	.160	4.06
6322UL	4	solid	C-250 C-500 1000	C-76 C-152 305	7.2 14.5 31.0	3.3 6.6 14.1	.010	.25	.183	4.64
6324UL	6	solid	U-1000 1000	U-305 305	44.0 46.0	20.0 20.9	.010	.25	.211	5.36
6326UL	8	solid	1000	305	63.0	28.6	.010	.25	.230	5.84
6328UL	10	solid	1000	305	73.0	33.1	.010	.25	.272	6.91
16 AWG										
6220UL*	2	solid	C-500 500 U-1000 1000	C-152 152 U-305 305	12.0 12.5 25.0 26.0	5.4 5.7 11.4 11.8	.010	.25	.174	4.42
6222UL	4	solid	500 1000	152 305	24.5 47.0	11.1 21.3	.010	.25	.204	5.18
14 AWG										
6120UL*	2	solid	500 1000	152 305	19.0 38.0	8.6 17.3	.011	.28	.205	5.21
6122UL	4	solid	500 1000	152 305	35.5 70.0	16.1 31.8	.011	.28	.241	6.12
12 AWG										
6020UL	2	solid	1000	305	59.0	26.8	.011	.28	.239	6.07

Shielded Multi-conductor (NEC FPLP)

18 AWG										
6320FL*	2	solid	C-500 U-1000 1000	C-152 U-305 305	10.5 22.0 22.0	4.8 10.0 10.0	.010	.25	.158	4.01
6322FL	4	solid	1000	305	36.0	16.4	.010	.25	.183	4.65
16 AWG										
6220FL*	2	solid	C-500 1000	C-152 305	14.5 31.0	6.6 14.1	.010	.25	.181	4.60
6222FL	4	solid	1000	305	58.0	26.3	.010	.25	.211	5.36
14 AWG										
6120FL*	2	solid	500 1000	152 305	23.5 45.0	10.7 20.4	.011	.28	.209	5.31
6122FL	4	solid	500 1000	152 305	42.0 77.0	19.1 35.0	.011	.28	.245	6.22
12 AWG										
6020FL	2	solid	500 1000	152 305	30.5 61.0	13.9 27.7	.011	.28	.243	6.17

*Also available in other jacket colors. Consult www.belden.com.

Fire Alarm Cable

Commercial Applications, Addressable Systems

Unshielded and Shielded, Plenum-Rated, Power-Limited, Mid-Capacitance



Unshielded Multi-conductor

FPLP Rated

Product Description

Bare copper conductors, FEP insulation, cabled together, Red Flammarrest® jacket with rip cord. Sequential footage marking every two feet.

Color Code: Black, Red.

Shielded Multi-conductor

FPLP Rated

Product Description

Bare copper conductors, FEP insulation, cabled together, Beldfoil® shield tape (aluminum side out) with tinned copper drain wire, Red Flammarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: Black, Red.

Specifications

Conductor	Bare Copper
Insulation	FEP
Shield (where applicable)	Beldfoil
Jacket	Flammarrest
Jacket Thickness	.015" (.381mm)
Approvals	
NEC	FPLP
California State Fire Marshall	
NEC Articles	760
Voltage Rating	300V
Temperature Rating	75°C
Nominal Capacitance*	
Unshielded†	26 pF/ft.
Shielded††	26–31 pF/ft.

*Capacitance between conductors.

†20% lower capacitance than cables on page 13.39

††60% lower capacitance than cables on page 13.39

Applications

- Addressable Fire Systems
- Data Circuits
- Monitor/Detection
- Control Circuits
- Initiating Circuits
- Notification Circuits

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC FPLP)

18 AWG										
6320UJ	2	solid	1000	305	16.0	7.3	.007	.18	.138	3.51
16 AWG										
6220UJ	2	solid	1000	305	24.0	10.9	.007	.18	.162	4.11
14 AWG										
6120UJ	2	solid	1000	305	32.0	14.5	.007	.18	.186	4.72


Shielded Multi-conductor (NEC FPLP)

18 AWG										
6320FK	2	solid								
			500	152	14.0	6.4	.018	.46	.185	4.70
			U-1000	U-305	28.0	12.7				
			1000	305	27.0	12.2				
16 AWG										
6220FK	2	solid	1000	305	37.0	16.8	.018	.46	.210	5.33

Unshielded



Shielded



Circuit Integrity in Conduit (CIC) Safe-T-Line® Cable

Commercial Applications, Addressable Systems
Unshielded, Riser-Rated

**Unshielded Multi-conductor**

FPLR-CIC Rated

Product Description

Bare copper conductors, ceramifiable silicone rubber insulation, Red FRPE (Low-Smoke, Non-Halogen) jacket. Sequential footage marking every two feet.

Color Code: Black, Red.

Specifications

Conductor	Bare Copper
Insulation	Silicone Rubber
Shield	Unshielded
Jacket	FRPE
Jacket Thickness	.035" (.889mm)
Approvals	
NEC	FPLR-CIC
NEC Articles	760
Voltage Rating	300V
Temperature Rating	105°C

Note: 2-conductor versions are color-coded black and red.
4 or more conductor versions are all black and numbered.

Applications

- Circuit Integrity
- Fire Alarm Circuit Integrity
- Survivability
- Survivability from Attack by Fire

Stranded**Solid**

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded Multi-conductor (NEC FPLR-CIC)**16 AWG**

5200UZ new	2	7	1000	305	68.0	30.9	.056	1.42	.37	9.40
-------------------------------------	---	---	------	-----	------	------	------	------	-----	------

5220UZ new	2	solid	1000	305	64.0	29.0	.056	1.42	.35	8.89
-------------------------------------	---	-------	------	-----	------	------	------	------	-----	------

14 AWG

5100UZ new	2	7	1000	305	87.0	39.5	.056	1.42	.40	10.16
-------------------------------------	---	---	------	-----	------	------	------	------	-----	-------

5120UZ new	2	solid	1000	305	79.0	35.8	.056	1.42	.38	9.65
-------------------------------------	---	-------	------	-----	------	------	------	------	-----	------

12 AWG

5000UZ new	2	7	1000	305	108.0	50.0	.056	1.42	.37	9.40
-------------------------------------	---	---	------	-----	-------	------	------	------	-----	------

5020UZ new	2	solid	1000	305	101.0	45.8	.056	1.42	.42	10.67
-------------------------------------	---	-------	------	-----	-------	------	------	------	-----	-------

FRPE = Flame-retardant Polyethylene

Audio Cable

Commercial Audio Systems
Shielded, Plenum-Rated



Shielded Multi-conductor CMP FT6 Rated or CL2P Rated

Product Description

Bare copper conductors, Flamarrest® insulation, conductors cabled, overall Beldfoil® tape shield (foil side out) and drain wire, Natural Flamarrest jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Insulation Thickness	
22 to 16 AWG	.009" (.229mm)
14 to 12 AWG	.011" (.279mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC (22 to 16 AWG)	CMP
CEC (22 to 16 AWG)	CMP FT6
NEC (14 to 12 AWG)	CL2P
NEC Articles	
22 to 16 AWG	800
14 to 12 AWG	725
Voltage Rating	
22 to 16 AWG	300V
14 to 12 AWG	150V
Temperature Rating	75°C


Applications

- Intercom/PA Systems
- Sound/Audio Systems

Solid Conductor



Stranded Conductor



Color Code Chart

(22 to 16 AWG)

Cond. No.	Color
1	Black
2	Red
3	White

(14 to 12 AWG)

Cond. No.	Color
1	Black
2	White
3	Red

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6520FE	2	solid	C-500	C-152	6.0	2.7	.015	.38	.122	3.10
			C-1000	C-305	12.0	5.4				
			U-1000	U-305	13.0	5.9				
			1000	305	13.0	5.9				
6500FE	2	7	C-500	C-152	5.5	2.5	.015	.38	.128	3.25
			U-500	U-152	7.0	3.2				
			500	152	7.0	3.2				
			C-1000	C-305	11.0	5.0				
			U-1000	U-305	13.0	5.9				
			1000	305	13.0	5.9				
6521FE	3	solid	1000	305	16.0	7.3	.015	.38	.129	3.28
6501FE	3	7	500	152	8.0	3.6	.015	.38	.135	3.43
			U-1000	U-305	16.0	7.3				
			1000	305	16.0	7.3				

20 AWG										
6420FE	2	solid	C-500	C-152	7.0	3.2	.015	.38	.134	3.40
			U-1000	U-305	16.0	7.3				
			1000	305	15.0	6.8				
6400FE	2	7	C-500	C-152	7.5	3.4	.015	.38	.142	3.60
			U-1000	U-305	17.0	7.7				
			1000	305	17.0	7.7				
6401FE	3	7	U-1000	U-305	21.0	9.5	.015	.38	.150	3.81
			1000	305	22.0	10.0				

18 AWG										
6320FE	2	solid	C-500	C-152	10.5	4.7	.015	.38	.150	3.81
			1000	305	22.0	10.0				
6300FE	2	7	C-500	C-152	11.0	5.0	.015	.38	.162	4.11
			U-500	U-152	12.0	5.4				
			500	152	12.0	5.4				
			U-1000	U-305	23.0	10.4				
			1000	305	23.0	10.4				
6301FE	3	7	U-500	U-152	15.5	7.0	.015	.38	.172	4.32
			U-1000	U-305	30.0	13.6				
			1000	305	31.0	14.1				

16 AWG										
6200FE	2	19	500	152	16.5	7.5	.015	.38	.184	4.67
			1000	305	33.0	15.0				
6201FE	3	19	500	152	22.5	10.2	.015	.38	.195	4.95
			U-1000	U-305	43.0	19.5				
			1000	305	45.0	20.5				

Shielded Multi-conductor (NEC CL2P)

14 AWG										
6100FE	2	19	500	152	25.0	11.3	.015	.38	.220	5.59
			U-1000	U-305	49.0	22.2				
			1000	305	51.0	23.2				
6101FE	3	19	1000	305	66.0	30.0	.015	.38	.234	5.94
12 AWG										
6000FE	2	19	500	152	36.0	16.4	.015	.38	.260	6.60
			1000	305	68.0	30.9				

Audio Cable

Pro Audio and Intercom Systems
Shielded, Plenum-Rated



Shielded Multi-conductor CMP FT6 Rated

Product Description

Bare copper conductors, FEP insulation, cabled with a Beldfoil® shield tape and drain wire. Natural Flamarrest® jacket.


Color Code: See chart below.

Specifications

Conductor	Bare Copper
Insulation	FEP
Insulation Thickness	
22 AWG	.0055" (.140mm)
20 AWG	.0060" (.152mm)
18 AWG	.0060" (.152mm)
Shield	Beldfoil
Jacket	Flamarrest
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Pro Audio
- Intercom/PA Systems
- Security Systems



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMP and CEC CMP FT6)

22 AWG										
6500FC	2	7	U-1000 1000	U-305 305	11.0 11.0	5.0 5.0	.015	.38	.116	2.95
6502FC	4	7	1000	305	18.0	8.2	.015	.38	.133	3.38
20 AWG										
6400FC	2	7	U-1000	U-305	15.0	6.8	.015	.38	.133	3.38
18 AWG										
6300FC	2	7	U-1000 1000	U-305 305	23.0 22.0	10.4 10.0	.017	.42	.155	3.94
6302FC	4	7	1000	305	34.0	15.5	.017	.42	.179	4.55

Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	White
4	Green

Audio Cable

Commercial Sound/Nurse Call Systems
Unshielded, Non-Plenum



**Unshielded,
Pairs or Multi-conductor**
CM Rated

Product Description

24 AWG solid bare copper conductors, polypropylene or polyolefin insulation, Dark Gray PVC jacket with rip cord.

Color Code: See Charts below.


Specifications

Conductor	Bare Copper
Insulation	
Multiconductor	Polypropylene
Paired	Polyolefin
Insulation Thickness	.0065" (.165mm)
Jacket	PVC
Nominal Capacitance	
Multiconductor	17 pF/ft.
Paired	15 pF/ft.
Approvals	
NEC	CM
CEC	CM
Voltage Rating	300V

Applications

- Nurse Call Systems
- Commercial Sound Systems
- Annunciators
- Voice Systems
- Paging

Paired



Multi-conductor



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Unshielded, Paired (NEC CM and CEC CM FT1)

24 AWG, Cat. 5e

5662UG new	6	solid	1000	304.8	16.0	8.62	—	—	.172	4.37
	(3/pr)									

Unshielded, Multi-conductor (NEC CM and CEC CM)

24 AWG

5626UG new	8	solid	1000	304.8	29.0	13.15	.030	.762	.093	2.36
									X	X
									.324	8.23
5624UG new	6	solid	1000	304.8	19.0	8.62	.024	.610	.081	2.06
									X	X
									.246	6.25

Color Code Chart

(5662UG)

Pair No.	Color Combinations
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green

Color Code Chart

(5626UG)

Cond. No.	Color
1	Yellow
2	Blue
3	Black
4	Orange
5	Red
6	Green
7	White
8	Purple

Color Code Chart

(5624UG)

Cond. No.	Color
1	Blue
2	Black
3	Orange
4	Red
5	Green
6	White



21 Residential Cables

Table of Contents

Residential Cables	Page No.
Introduction	21.2
Composite Data, Audio, Video, Security and Control Cable	21.3–21.8
Banana Peel® Jacketless Cables: Category 5e	21.3
Jacketed Cables: Category 5e and 5	21.5
Siamese Cables: Category 5e and 5	21.7
Keypad and Control Cables: Category 5e and 5	21.8
Data and Voice Cable	21.9–21.11
Category 6: 23 AWG UTP	21.9
Enhanced Category 5e: 24 AWG Bonded-Pair & UTP	21.10
Category 5e: 24 AWG UTP	21.11
Video Cable	21.12–21.16
Broadband CATV and DBS Coax: RG-6/U Type, 18 AWG	21.12
Precision Video Coax: RG-6/U Type, 18 AWG	21.14
Precision Video Coax: RG-59/U Type, 20 AWG	21.14
Precision Video Coax: Subminiature RG-59/U Type, 23 AWG	21.15
Standard Analog Coax: RG-59/U Type, 23 AWG	21.15
Bundled RGB Coax: Miniature, 25 AWG	21.16
BananaPeel® RGB Coax: Mini Hi-Res, 25 AWG	21.17
High-Flex S-Video Coax: 30 AWG	21.19
Speaker Cable	21.20–21.23
Low-Cap, OFHC Multi-conductor: 16 to 10 AWG	21.20
Multi-conductor: 16 to 12 AWG	21.21
High-Strand Multi-conductor: 16 to 10 AWG	21.22
High-Conductivity ETP Copper, Parallel: 16 to 12 AWG	21.23
Alarm, Security and Speaker Cable	21.24
Multi-conductor: 22 AWG	21.24
Multi-conductor: 18 AWG	21.24
Shielded Audio Cable	21.24
AES/EBU Digital Audio Cables: 24 AWG	21.24
Audio and Control Interconnect Cables: 22 AWG	21.24
Surveillance Coax	21.25
Coax: RG-59/U Type, 20 AWG	21.25
Composite: RG-59/U Type, 20 AWG	21.25
Composite: RG-6/U Type, 18 AWG	21.25
Tools and Accessories	21.26